



* OVERALL LENGTH: FOR 30, 40, 50, & 60 dB UNITS

30 & 40 dB = 0.98 INCH

50 & 60 dB = 1.36 INCH

ELECTRICAL:

NOMINAL IMPEDANCE (OHMS)	50
AVERAGE POWER RATING (MAX. WATTS +25°C)	2.0*
PEAK POWER (MAX. WATTS)	500**
CONNECTOR DURABILITY (MIN. CYCLE)	500
ENGAGEMENT/DISENGAGEMENT (MAX. IN. LBS.)	2.0

* POWER INPUT DERATED LINEARLY FROM 25°C TO .5 WATT AT 125°C.
 ** PEAK POWER FOR A DUTY CYCLE OF 5×10^{-4} MAXIMUM PULSE DURATION OF 5 MICROSECONDS.

ENVIROMENTAL:

OPERATING TEMPERATURE RATING (DEGREE CENTIGRADE)	-65°C TO +125°C
VIBRATION (MIL-STD-202, METHOD 204. COND. D. 20G'S)	
SHOCK (MIL-STD-202, METHOD 213. COND. I. 100G'S)	
TEMPERATURE CYCLING (MIL-STD-202. METHOD 107, COND. B. -65C TO 125°C)	
MOISTURE RESISTANCE (MIL-STD-202. METHOD 106. LESS STEP 7B)	

MATERIAL & FINISH:

BODIES AND COUPLING NUT: STAINLESS STEEL PER AMS-5640. UNS S30300. TYPE I. PASSIVATED PER QQ-P-35C. TYPE II

CONTACTS: BERYLLIUM COPPER PER ASTM-B196. COND. TD04. ALLOY UNS-C17300: GOLD PLATED PER MIL-G-45204. TYPE I. GRADE C. CLASS I: OVER NICKEL PER QQ-N-290. CLASS I.

LOCK RING: BERYLLIUM COPPER PER ASTM-B196. COND. TD04. ALLOY UNS-C17300.

BELLOWS SPRING: ELECTRO DEPOSITED NICKEL: GOLD PLATED

RESISTOR ELEMENT: ALUMINUM NITRIDE SUBSTRATE WITH TANTALUM NITRIDE RESISTOR: GOLD PLATED TERMINATIONS.

ELEMENT SLEEVE: BRASS PER ASTM-B16, ALLOY 360. GOLD PLATED PER MIL-G-45204. TYPE I. GRADE C. CLASS 1: OVER NICKEL PER QQ-N-290. CLASS I.

INSULATORS: NORYL EN265.

GASKET: RUBBER SILICONE PER ZZ-R-756. CLASS IIB. GRADE 50-60.

ELECTRICAL CHARACTERISTICS

dB VALUE	ATTENUATION ACCURACY	VSWR MAX.			
		DC-4 GHz	4-8 GHz	8-12.4 GHz	12.4-8 GHz
.5 - 8 dB	+/- .3 dB	1.15:1	1.25:1	1.25:1	1.35:1
9 - 20 dB	+/- .5 dB				
30 & 40 dB	+/- .85 dB				
50 & 60 dB	+/- .85 dB				

RF Depot.com Inc.



Your RF & Microwave Supermarket
10101 E. Bacon Drive, Beltsville, MD 20705

Web Site: rfdepot.com
E-mail: rfdepot@rfdepot.com
(877) 733-3768 (877-RF Depot)

TOLERANCE

X.XX= .05
X.XXX= .005
ANGLE= 2 ± °

FINISH

DWN 8-15-05
F.G.

DES

APP

CHK

NEXT ASSEMBLY

CODE IDENT: 9V554 FSCM 64998

ATTENUATOR
SMA JACK TO SMA PLUG

A

RFD-3699-XX